

# Compress Tape 10 mm

Art.: 05.0348.0000

Roll 12 m

Compress Tape is a specially developed expanding tape used to fix general rattles, and to remove all kinds of whistling noises and vibrations, which are often caused by the wind or a given engine speed.



Base:	Fire-retarding PU ester impregnated with microcrystalline wax
Density:	± 100 kg/m <sup>3</sup>
Dimensions:	10 mm x 12 m
Temperature resistance:	-20°C to +85°C
Water resistance:	Good
Saltwater resistance:	Good
Solvent resistance:	Moderate
Acid resistance:	Resistant to weak acids
Tests:	Satisfies fire class standard: B1 (according to DIN 4102). UV resistant and downpour proof for joints between 2 and 3 mm – overpressure up to 300 Pa.
Application conditions:	No limit. The expansion time is affected by the temperature, sunlight and age of the product. <u>Expansion time 5°C:</u> 20% (1 day); 50% (7 days); 90% (10 days) <u>Expansion time 20°C:</u> 20% (20 minutes); 50% (27 minutes); 90% (10 hours) <u>Expansion time 30°C:</u> 20% (2 minutes); 50% (20 minutes); 90% (4 hours)
Type of surface:	The most common surfaces
Surface preparation:	The surface must be clean, dry and free of grease. Degrease surfaces with Innotec <a href="#">Multisol</a> or Innotec <a href="#">Seal and Bond Remover</a> .
Application method:	Cut off the required length. Remove the protective film and lay the tape on the surface. When mounting the tape between parts, complete assembly as quickly as possible.
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	12 months in original, unopened packaging
Storage conditions:	Store cool and dry, at a temperature between +5°C and 20°C
Type of batchcode:	F
EAN Code:	5400563025888





This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

